

Specification Parallel compressor Rack Systems

Model	Refrigerating Capacity (Kw)				Dimensions(mm)			Weight(kg)	V/Ph/Hz	Refrigerant
	Evaporation Temperature °C				L	W	H			
	-35.00	-25.00	-10.00	0.00						
SRS-2-06	5.01	8.69	16.86	24.60	1300	800	1200	291	400/3/50	R404A
SRS-2-10	6.83	11.51	22.40	33.10	1500	860	1200	332	400/3/50	R404A
SRS-2-14	10.35	17.47	33.90	49.80	1500	860	1200	347	400/3/50	R404A
SRS-2-20	11.88	21.20	42.90	64.20	1500	1200	1250	458	400/3/50	R404A
SRS-2-30	16.08	29.00	59.30	89.10	1500	1300	1250	474	400/3/50	R404A
SRS-2-40	20.40	35.50	70.80	105.40	1500	1300	1250	500	400/3/50	R404A
SRS-2-50	28.20	48.30	93.50	136.90	2200	1400	1350	616	400/3/50	R404A
SRS-2-60	32.80	55.80	107.50	157.10	2200	1400	1350	632	400/3/50	R404A
SRS-2-70	41.50	71.00	137.20	201.00	2500	1500	1350	700	400/3/50	R404A
SRS-2-80	48.30	81.80	156.60	228.00	2500	1500	1350	716	400/3/50	R404A
SRS-3-09	7.51	13.04	25.30	36.90	1800	800	1300	391	400/3/50	R404A
SRS-3-15	10.24	17.27	33.60	49.70	2100	860	1300	448	400/3/50	R404A
SRS-3-21	15.53	26.20	50.80	74.70	2100	860	1300	465	400/3/50	R404A
SRS-3-30	17.82	31.80	64.40	96.30	2100	1200	1350	627	400/3/50	R404A
SRS-3-45	24.10	43.50	88.90	133.60	2100	1300	1350	646	400/3/50	R404A
SRS-3-60	30.50	53.20	106.10	158.10	2100	1300	1350	680	400/3/50	R404A
SRS-3-75	42.20	72.40	140.20	205.00	2500	1400	1450	849	400/3/50	R404A
SRS-3-90	49.20	83.70	161.20	236.00	2500	1400	1450	868	400/3/50	R404A
SRS-3-105	62.30	106.50	206.00	301.00	3000	1500	1450	965	400/3/50	R404A
SRS-3-120	72.50	122.60	235.00	342.00	3000	1500	1450	984	400/3/50	R404A