

Technical Specifications Fiber Glass Cooling Towers Model SFCT

MODEL	TONAGE	AIR	DIMENSIONS		FAN		WATER	WEIGHTS	
		Flow	Diameter	Height	Power	Diameter	Flow	Empty	Full
		CFM	mm	mm	HP	mm	GPM	Kg	Kg
SFCT- 20	20	7250	1500	1800	0.5	750	70	145	275.5
SFCT- 30	30	8500	1800	2000	1	825	100	220	418
SFCT- 40	40	9400	1800	2000	1	825	140	250	475
SFCT- 50	50	11350	2100	2500	1.5	1170	175	320	608
SFCT- 60	60	14550	2100	2500	2	1170	205	370	703
SFCT- 80	80	18000	2100	2500	2	1170	280	400	760
SFCT- 100	100	24800	2600	2680	3	1200	335	525	945
SFCT- 125	125	28000	2950	2850	4	1450	430	625	1125
SFCT- 150	150	30000	2950	2850	4	1450	515	700	1260
SFCT- 175	175	33500	3700	2950	4	1700	600	900	1620
SFCT- 200	200	48000	3700	2950	5.5	1700	690	1045	1881
SFCT- 225	225	58000	3700	2950	5.5	1700	775	1190	2142
SFCT- 250	250	67000	4400	3600	7.5	2000	865	1300	2210
SFCT- 300	300	78000	4400	3600	7.5	2000	1025	1500	2550
SFCT- 350	350	84000	4850	3750	7.5	2300	1200	1625	2762.5
SFCT- 400	400	91500	4850	3750	10	2300	1390	1875	3187.5
SFCT- 450	450	108000	5500	3950	15	3000	1565	1990	3383
SFCT- 500	500	121000	5500	3950	15	3000	1750	2050	3485
SFCT- 600	600	140000	6550	4800	15	3250	2125	2450	3920
SFCT- 700	700	170000	6550	4800	20	3250	2465	2600	4160
SFCT- 800	800	198000	7600	5300	25	3500	2850	3000	4800
SFCT-1000	1000	218000	7600	5300	30	3500	3525	3300	5280